



# 626 CARPET & SHEET VINYL ADHESIVE REMOVER

V.O.C. COMPLIANT

Sentinel 626 Carpet & Sheet Vinyl Adhesive Remover is a powerful, water based, biodegradable formulation designed specifically for quickly removing latex, acrylic, and pressure sensitive indoor adhesives from concrete, terazzo, ceramic and vinyl tile or wood substrates.

## Application Information (Always follow product label instructions for best results)

Review directions and precautions thoroughly before starting work.

### USE CONDITIONS

This product works best at room temperature (70°F). Colder temperatures can affect product performance.

### REMOVAL OF LATEX, ACRYLIC AND PRESSURE SENSITIVE ADHESIVES:

**Step 1:** Apply 626 directly onto adhesive. Use a broom, mop or squeegee to agitate and maintain even coverage while keeping the surface wet. Allow 626 to soak and penetrate for 30-60 minutes.

**Step 2:** Scrape softened adhesive from the floor with a razor floor scraper. Repeat steps 1 and 2 if glue is especially thick or stubborn. Dispose of all waste following all local, state and federal regulations.

**Step 3:** Rinse the subfloor thoroughly with clean water. Allow surface to completely dry and test moisture levels before reflooring.

### REMOVAL OF SHEET VINYL OR LINOLEUM BACKING:

Once the wear layer is removed, mix 1 part HOT water to 4 parts 626. Apply directly to the backing and allow to soak through. Maintain even coverage and a wet surface for 1-2 hours or until backing and adhesive can easily be removed with a razor floor scraper. Rinse the surface with clean water and allow to dry. Test moisture levels before reflooring.

### REMOVAL OF CARPETING:

Using a utility knife, cut the carpeting into strips 1 foot wide, making sure to cut all the way through to the subfloor. Mix 2 parts HOT water to 1 part 626 and pour directly onto carpet. Maintain even coverage and completely saturate carpeting. Allow to soak for 4 hours up to overnight. (If soaking overnight, covering the carpet with poly will help control evaporation and drying.) When carpet releases easily, roll up and remove. Follow latex removal steps to remove remaining adhesive.

### WARRANTY

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

## SPECIFICATIONS

<b>Physical State:</b>	Liquid
<b>Appearance:</b>	Clear
<b>Color:</b>	None
<b>Odor:</b>	No odor
<b>pH:</b>	10.5 - 11.5
<b>Flash Point:</b>	None to boiling
<b>Boiling Point:</b>	212°F
<b>V.O.C. Content:</b>	<15g/L (calc.)*
<b>Shelf Life:</b>	60 Months
<b>Coverage Rate:</b>	25-70 sq. ft./gal dependent on application

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.



Watch 626 in action!



**800-373-0633 or [www.senpro.com](http://www.senpro.com)**

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445